


## Environmental Control Unit Accessories

## Switch Description

Bebco Model EDS Explosion-Proof Disconnects provide three 30 amp poles to remove all power safely from Model EAC Enclosure Air Conditioners, Model TAC & THP Through Wall Air Conditioners and Heat Pumps, Model ECH Enclosure Convection Heaters and other Bebcos Products. These switches are intended and suitable for mounting on or near the exterior surface of the enclosure to safely disconnect power from these devices.

## Technical Specifications

Contact Rating:	30 Amps, Maximum
Circuit Wiring:	3-Pole, No Fused
Body Material:	Cast Aluminum
Cover Material:	Thermoplastic
Operator Paddle:	Phenolic Toggle
Overall Height:	6.36 Inches
Overall Width:	3.95 Inches
Overall Depth:	4.35 Inches
Switch Action:	Maintained Position
Voltage Rating:	600 VAC / 230 VDC, Maximum
Circuit Rating:	5000 Amp Short Circuit Rating
Terminal Type:	Screw Clamp Terminals
Lockout Method:	Padlock Shackle Hole
Mounting Style:	2-Point Surface Mount
Conduit Ports:	Top & Bottom, 3/4" Female Thread
Certifications:	UL Listed, CSA Certified, CE Marked



# Model EDS

## Electrical Disconnect Switches

### Class I, Division 1, Group B, C & D

### Unit Power Disconnects

Technical Bulletin EDS TB-R0
© 04.21.2019



**Model EDS**  
Power Disconnect



**IMPORTANT NOTES:** All specifications subject to change without notice. Warranty & Liability policies available upon request.



**Bebco Environmental**  
Hazardous & Industrial Climate Control Solutions

4725 Lawndale • La Marque, Texas 77568

Phone: 1.844.EXP.HVAC • 1.844.397.4822  
www.exphvac.com • sales@exphvac.com